


PRODUCT DATA SHEET



A) SPECIFICATIONS

- 1 Stainless steel bow
Hooking on on L shaped
angular support 40x40mm
- 2 Self-locking pressure screw M6
- 3 Stainless steel sliding pressure plate.
- 4 SAS black P.A. fiberglass saddles

B) RESISTANCE TESTS

UV Test BS-ISO 105-B06
Vibration test conforming to UNI 60068-2-6
Operating temperature: -30°C +120°C

C) PACKAGING INFORMATION

Packing in boxes.
Label indicating:
product code, article, quantity,
production batch,
FIMO logo and figure.
(Customer code on request).

D) MOUNTING INSTRUCTIONS

IST026

CODE	ARTICLE	ø D	L	H	BOX	WEIGHT
61 1551 0206	sRF A4/ 2x6	5 - 6	12	33	50	70
61 1551 0207	sRF A4/ 2x7	6 - 7	12	33	50	70
61 1551 0208	sRF A4/ 2x8	7 - 8	12	33	50	70
61 1551 0209	sRF A4/ 2x9	8 - 9	12	33	50	70
61 1551 0291	sRF A4/ 2x9 M	9 - 10	12	33	50	70
61 1551 0210	sRF A4/ 2x10	10 - 11	12	33	50	70
61 1551 0211	sRF A4/ 2x11	10 - 11	22	63	50	103
61 1551 2012	sRF A4/ 2x12	11 - 12	22	63	50	103
61 1551 0213	sRF A4/ 2x13	12 - 13	22	63	50	100
61 1551 0214	sRF A4/ 2x1 1/2" S (14)	13 - 14	22	63	50	105
61 1551 0238	sRF A4/ 2x3/8" (16)	15 - 16	22	63	50	100
61 1551 0212	sRF A4/ 2x1 1/2" (17)	16 - 17	22	63	50	99
61 1551 0258	sRF A4/ 2x5/8" (23)	21 - 23	34	87	25	209
61 1551 0227	sRF A4/ 2x7/8" S (27)	26 - 27	34	87	25	169
61 1551 0278	sRF A4/ 2x7/8" (28)	27 - 28	34	87	25	169
61 1551 2178	sRF A4/ 2x7/8" M (30)	29 - 30	34	87	50	159
61 1551 2118	sRF A4/ 2x1.1/8" (38)	36 - 38	46	111	25	265
61 1551 2114	sRF A4/ 2x1.1/4" (40)	39 - 40	46	111	25	252
61 1551 2148	sRF A4/ 2x1.5/8" S (49)	48 - 49	58	137	25	363
61 1551 2158	sRF A4/ 2x1.5/8" (52)	50 - 52	58	137	25	361
61 1551 2214	sRF A4/ 2x2.1/4" (60)	59 - 60	70	161	25	431
61 1551 0262	sRF A4/ 2x62	60 - 62	70	161	25	412

RI	DATE	DR	DATE	AP	Description:
02					<i>Stainless cable clamps type sRF A4 For 2 coaxial cables, complete with 4 calibrated saddles. For articles see schedule.</i>
01	02/12/2021	E.N.	02/12/2021	A.V.	
	UPDATED BOX QUANTITY				
00	01/02/16	G.S.	01/02/16	A.V.	
	1 ST EMISSION				
					<i>Use: Fastening of 2 coaxial cables to angular 40 x 40 mm.</i>