PRODUCT DATA SHEET



A) SPECIFICATIONS

1 *Stainless steel bow*
Hooking on flat and round 3-12mm
2 *Self-locking pressure screw M6*
3 *Stainless steel sliding pressure plate.*
4 *DAS/DAT black P.A. saddles*

B) RESISTANCE TESTS

UV Test BS-ISO 105-B06
Vibration test conforming to UNI 60068-2-6
Operating temperature: -30°C +120°C

C) PACKAGING INFORMATION

Packing in boxes.
Label indicating:
product code, article, quantity,
production batch,
FIMO logo and figure.
(Customer code on request).

D) MOUNTING INSTRUCTIONS

IST026

CODE	ARTICLE	ø D	L	H	WEIGHT
61 1582 0205	mRF B/ 2x5	4 - 5	12	39	38
61 1582 0206	mRF B/ 2x6	5 - 6	12	39	38
61 1582 0207	mRF B/ 2x7	6 - 7	12	39	38
61 1582 0208	mRF B/ 2x8	7 - 8	12	39	38
61 1582 0209	mRF B/ 2x9	8 - 9	12	39	34
61 1582 0210	mRF B/ 2x10	10 - 11	12	39	34
61 1582 0212	mRF B/ 2x1/2" (17)	16 - 17	22	63	99
61 1582 0278	mRF B/ 2x7/8" (28)	27 - 28	34	87	169

RI	DATE	DR	DATE	AP
02				
01				
00	29/01/16	G.S.	29/01/16	A.V.
	1ST EMISSION			

Description:

Stainless cable clamps type mRF B
For 2 coaxial cables, complete with 2 calibrated saddles.
For articles see schedule.

FIMO
Building Sustainable Innovation

RoHS
Compliant · RoHS 2002/95/EC

Use:

Fastening of 2 coaxial cables.
Hooking on flat and round 3-12mm

FI.MO.TEC. S.p.a. reserves the right to modify the technical specifications without prior notice, according to the technical progress
Copyright FI.MO.TEC. S.p.a. All rights reserved.