


PRODUCT DATA SHEET



A) SPECIFICATIONS

- 1 Stainless steel bow
Hooking on section 40x22mm
- 2 Self-locking pressure screw M6
- 3 Stainless steel sliding pressure plate.
- 4 DAS/DAT black P.A. saddles

B) RESISTANCE TESTS

UV Test BS-ISO 105-B06
Vibration test conforming to UNI 60068-2-6
Operating temperature: -30°C +120°C

C) PACKAGING INFORMATION

Packing in boxes.
Label indicating:
product code, article, quantity,
production batch,
FIMO logo and figure.
(Customer code on request).

D) MOUNTING INSTRUCTIONS

IST026

CODE	ARTICLE	ø D	L	H	WEIGHT
61 1581 0005	mRF C/ 1x5	4 - 5	12	24	28
61 1581 0006	mRF C/ 1x6	5 - 6	12	24	28
61 1581 0007	mRF C/ 1x7	6 - 7	12	24	28
61 1581 0008	mRF C/ 1x8	7 - 8	12	24	28
61 1581 0009	mRF C/ 1x9	8 - 9	12	24	25
61 1581 0010	mRF C/ 1x10	10 - 11	12	24	25
61 1581 0012	mRF C/ 1x1/2" (17)	16 - 17	22	34	55
61 1581 0078	mRF C/ 1x7/8" (28)	27 - 28	34	46	85

RI	DATE	DR	DATE	AP	Description: Stainless cable clamps type mRF C For 1 coaxial cable, complete with 1 calibrated saddles. For articles see schedule.
02					
01					
00	29/01/16	G.S.	29/01/16	A.V.	
	1 ST EMISSION				
					Use: Fastening of 1 coaxial cable. Hooking on section 40x22mm